

# Luxury Vinyl Tiles

Waterproof

Superior Acoustic Performance

Tru-Grain Technology

Easy installation system

[WWW.TARKETT.COM.AU](http://WWW.TARKETT.COM.AU)

**iD INSPIRATIONS  
ULTIMATE**

 **Tarkett**

# TECHNICAL DATA SHEET

Certification & classification	Standards	iD Inspirations Ultimate
Type of floor covering	EN ISO 10582	Heterogeneous Compact Resilient Floorcovering
Classification	EN ISO 10874	Domestic: 23 Commercial: 33 Industrial: 42
Technical characteristics		
Total thickness	EN ISO 24346	6.5 mm
Wear layer thickness	EN ISO 24340	0.55 mm
Total weight	EN ISO 23997	11.3 kg/m <sup>2</sup>
Wear layer binder content	EN ISO 10582	Type I
Dimensions	EN ISO 24342	Planks 176 x 1213 mm 6 planks/box = 1.28 m <sup>2</sup> Tiles 300 x 600 mm 7 tiles/box = 1.26 m <sup>2</sup>
Surface treatment (PUR)		Yes - PUR Ultimate
Beveled edges		Yes - 4 Bevels
Technical performances		
Dimensional stability	EN ISO 23999	Average measured value 0.05% Required value ≤ 0.15%
Curl resultant to heat	EN ISO 23999	≤ 1 mm
Reaction to fire	ISO AS 9239-1	Critical radiant flux 10.3 kW/m <sup>2</sup> Smoke 230 % min
Residual indentation	EN ISO 24343-1	≤ 0.05 mm
Furniture leg	EN 424	No damage
Castor chair	ISO 4918 - EN 425	No damage
Impact sound reduction	EN ISO 717-2	ΔL <sub>w</sub> 19 dB
Reduction of in-room impact noise	EN ISO 31-074	Class C (L <sub>n,e,w</sub> < 85 dB)
Thermal resistance	EN ISO 10456	0.05 m <sup>2</sup> K/W
Light fastness	EN ISO 105-B02 (method 3a)	≥ 6
Chemical resistance	EN ISO 26987	Very Good
Slip resistance	AS 4586:2013 DIN 51130/EN 13893	P2/P3 dependent on embossing R9
Electrical properties	EN 1815	≤ 2 kV
Peeling resistance	EN ISO 24345	≥ 50N / 50mm
Underfloor heating		Suitable - max. 27 °C

The above information is subject to modification for the benefit of further improvement. (09/18).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.



Produced under license from I4F  
<https://i4f-patents.com>



Disclaimer: Please note that products in photos are installed for creative purposes and not according to technical specifications. Please refer to Tarkett installation instructions for guidance.

Contact: Tarkett Australia  
P: 1300 851 484  
E: [customerservice@tarkett.com](mailto:customerservice@tarkett.com)  
W: [www.tarkett.com.au](http://www.tarkett.com.au)

